

FEATURES

- LED long life
- Extra bright
- Continuously rated
- Wide operating voltage
- 120° prime light output from vertical axis
- Dustproof & submersible in water

Visual Signals LIGHT EMITTING DIODE

RS Stock No.:



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

The LED80 incorporates 12 ultra bright Surface Mount LEDs offering an economic solution for a wide range of general signalling solutions. Ideally suited for local indication the beacon is controlled by either two wires (flashing mode) or three (static mode). The beacons are supplied fully assembled and ready for immediate installation. The unit offers two mounting options, either Stud Mount or Surface Mounting using the two piece fixing plate supplied. One plate is fixed to the appropriate surface the other to the beacon, the two plates then 'Snap Fit' together.

General Specifications

Bulb Type	LED
Light Effect	Flashing, Steady
Lens Colour	Red
Housing Colour	Black
Lamp Include	Yes
Multifunction	Yes
Series	LED 80

Electrical Specifications

Supply Voltage	10 → 100 VDC , 115VAC-230VAC
Current Type	DC ,AC
Current Consumption	90 mA Flashing 200 mA Static at 24v Dc 20mA

Mechanical Specifications

Height	50mm
Base Diameter	76mm
Mounting Style	Surface Mount

Protection Category

IP Rating	IP 67
-----------	-------

Approvals

Standards Met	RoHS Compliant
---------------	----------------



