

Datasheet

## RS Pro 250mA Radial Non-Resettable Wire Ended Fuse, 250 V

RS Stock No: **767-5193**



### Product Details

RS Pro radial non-resettable fuse withstands currents up to 250 mA and voltages up to 250 V. It has thermoplastic body for added durability. This fast acting fuse forms a convenient and reliable solution to a vast array of application requirements.

### Features and Benefits

- Fast acting fuse
- Non-resettable
- Radial fuse
- Wire-ended

**Specifications:**

|   |                         |
|---|-------------------------|
| Body Diameter                                 | 8.35 mm                 |
| Body Height                                   | 7.7 mm                  |
| Body Material                                 | Thermoplastic           |
| Breaking Capacity (at Maximum Voltage Rating) | 35 A at 250 V ac        |
| Current Rating                                | 250 mA                  |
| Lead Orientation                              | Radial                  |
| Maximum Operating Temperature                 | +125°C                  |
| Minimum Operating Temperature                 | -55°C                   |
| Voltage Rating                                | 250 V                   |
| Voltage Rating                                | 250 V                   |
| Wire Diameter                                 | 0.62 mm                 |
| Wire Length                                   | 22 mm                   |
| Wire Pitch                                    | 5.08 mm                 |
| Fuse Type                                     | Fast Acting             |
| Nominal Resistance                            | 0.7007 $\Omega$         |
| Standards Met                                 | VDE, CSA, UL, CCC, RoHS |