


## **ENGLISH**

Datasheet

RS Pro 2 Core Orange Unscreened 3182Y Stranded PVC Mains Power Cable H05VV-F, 1 mm<sup>2</sup> CSA 10 A 100m, 500 V RS Stock No: 491-964



## **Product Details**

RS Pro BASEC 2 core unscreened stranded PVC mains power cable in orange colour, is 100 m long with 1 mm<sup>2</sup> cross sectional area. The power cable has 10 A of current rating and 500 V of voltage rating. This harmonised, flexible power cable is suitable for indoor installations. The power cable meets BS6500, CENELEC HD21.5 and BASEC standards.

## **Features and Benefits**

- Flexible cordage
- Suitable for use in homes, offices etc
- Copper conductor



## ENGLISH

| Specifications:               |   |
|-------------------------------|---|
| American Wire Gauge           | 17 AWG  |
| Cable Shape                   | Multicore   |
| Conductor Material            | Copper  |
| Conductor Resistance          | 19.5 Ω/km   |
| Conductor Strand Type         | Stranded  |
| Core Strands                  | 32/0.2 mm   |
| Cross Sectional Area          | 1 mm <sup>2</sup>                                 |
| Current Rating                | 10 A  |
| Drain Wire                    | No  |
| Harmonised Code               | H05VV-F   |
| Insulation Material           | PVC   |
| Length                        | 100 m   |
| Maximum Operating Temperature | +70°C   |
| Minimum Operating Temperature | -15°C   |
| Number of Cores               | 2   |
| Number of Strands             | 32  |
| Operating Temperature Range   | -15 to +70°C                                      |
| Outer Diameter                | 7.5 mm  |
| Reel Length                   | 100 m   |
| Screened/Unscreened           | Unscreened  |
| Sheath Colour                 | Orange  |
| Sheath Material               | PVC   |
| Size of Strands               | 0.2 mm  |
| Standards Met                 | BASEC, BS 6500, CENELEC HD21.5,<br>RoHS Compliant |
| Туре                          | 3182Y   |
| Voltage Rating                | 500 V   |
|                               |   |