

FEATURES

- Used commercially in applications including pressurised water system
- Central heating system and air compression requirement
- Extruded, calendered film tapes that resist curling during unwind and provide an exceptionally smooth surface when applied
- Extruded PTFE film tapes lie flatter than typical skived PTFE film tape
- High temperature and chemical resistance enables performance on heated machinery and equipment
- Excellent abrasion resistant surface

RS PRO High & Low Temperature Grey PTFE Tape 25mm x 33m x 0.08mm

Minimum Operating Temperature -54°C

Maximum Operating Temperature +260°C

RS Stock No.: 208-8432



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Family Name

Product Description

PTFE Tape 25mm x 33m x 0.08mm
 Width 25mm
 Thickness 0.08mm
 Length 33m
 Colour grey
 Minimum Operating Temperature -54°C
 Maximum Operating Temperature +260°C

Mechanical specification

Dimension	25mm x 33mm x 0.08mm (T)
Minimum operation	-54°C
Maximum operation	+260°C

Physical property

Surface film	UV table PVC film
Adhesive	High grade solvent acrylic
Service temperature	+15°C to 25°C
Service temperature	-30°C to +70°C
Adhesion	0.8kgs/100mm, 5 minutes, 20mm
Shrinking	10min, shrinking rate <0.8mm, in 24hr, shrinking rate<3.2mm

Additional Information

Custom Tariff Number HS Code	39191080
-------------------------------------	----------

Similar Products

Stock No.	Brand	Product Name	Attribute 1	Attribute 2	Attribute 3
2088433	RS PRO	PTFE tape	Width 50mm	Length 33m	Thickness 0.08mm

Connection Diagrams / Assembly Diagrams / Illustrations / Accessories