



Serial Cards & Adapters

If you're looking for a simple, cost-effective way to connect serial devices in your industrial application or server room, our Serial Cards and Adapters make it easy to add Serial ports (RS-232, RS-422, RS-485 etc.) to your computer through common expansion ports such as PCI and PCI Express, as well as through USB.

StarTech.com #	RS #	Input Port	Output Port	Number of Ports	Max Baud Rate	Bus Type	Length	Serial Protocol	Chipset	LED
ICUSB232INT1	186-4061	USB Motherboard Header	RS232	1	115.2kbit/s	USB 2.0	0.6m	RS-232	FTDI - FT232RL	-
ICUSB2328I	179-7979	USB-A	RS232	8	921.6kbit/s	USB 2.0	-	RS-232	FTDI - FT232RL	Power
ICUSB128410	193-2835	USB-A	Centronics (36 pin)	1	-	USB 2.0	3m	-	Prolific - PL2305	-
ICUSB23208FD	186-4056	USB-A	RS232	8	921kbit/s	USB 2.0	0.9m	RS-232	FTDI - FT4232	Data Transmit, Data Receive
ICUSBCPLLD25	186-4053	USB-C	DB 25	1	1.5Mbps	USB-C	-	-	Prolific - PL2305	-
ICUSB232C	179-7978	USB-C	RS232	1	921.6kbit/s	USB-C	-	RS-232	Prolific - PL2303RA	-
ICUSB232SM3	179-7973	USB-A	RS232	1	921.6kbit/s	USB 2.0	0.9m	RS-232	Prolific - PL2303GC	-
ICUSB234854I	186-4064	USB-A	RS232/422/485	4	921.6kbit/s	USB 2.0	-	RS-232/422/485	FTDI - FT4232H	Port Mode, Port Send, Port Receive, Power
ICUSB232V2	179-7972	USB-A	RS232	1	921.6kbit/s	USB 2.0	-	RS-232	Prolific - PL2303GT	-
IC232485S	186-4060	RS232	RS422/485	1	921.6kbit/s	USB 2.0	-	RS-232/422/485	-	Power, Rx, Tx
ICUSB2322I	179-7981	USB-A	RS232	2	921.6kbit/s	USB 2.0	1.8m	RS-232	FTDI - FT232RL	Rx, Tx
ICUSB422	123-8050	USB-A	RS422/485	1	921.6kbit/s	USB 2.0	1.8m	RS-422/485	FTDI - FT232RL	-
ICUSB1284D25	193-2834	USB-A	DB 25	1	-	USB 2.0	1.8m	-	Prolific - PL2305	-
RS232EXTC1GB	186-4059	RS232	RS232	1	115.2kbit/s	USB 2.0	-	-	-	-

StarTech.com #	RS #	Input Port	Output Port	Number of Ports	Max Baud Rate	Bus Type	Length	Serial Protocol	Chipset	LED
ICUSB422IS	179-7971	USB-A	RS422/485	1	921.6kbit/s	USB 2.0	1.8m	RS-422/485	FTDI - FT232RL	-
ICUSB2321FIS	179-7984	USB-A	RS232	1	921.6kbit/s	USB 2.0	2.5m	RS-232	FTDI - FT232RL	-
ICUSB232D	179-7976	USB-A	RS232	1	128kbit/s	USB 2.0	1.8m	RS-232	Prolific - PL2303TA	-
ICUSB2322F	179-7982	USB-A	RS232	2	921.6kbit/s	USB 2.0	1.8m	RS-232	FTDI - FT2232D	-
ICUSB2324	186-4058	USB-A	RS232	4	921kbit/s	USB 2.0	1.8m	RS-232	FTDI - FT232RL	-
ICUSB2324852	186-4057	USB-A	RS232/422/485	2	921.6kbit/s	USB 2.0	-	RS-232/422/485	FTDI - FT2232H	Power
ICUSB234858I	186-4065	USB-A	RS232/422/485	8	921.6kbit/s	USB 2.0	-	RS-232/422/485	FTDI - FT4232H Genesys Logic - GL825	Port Mode, Port Send, Port Receive, Power
ICUSB232PRO	179-7974	USB-A	RS232	1	921kbit/s	USB 2.0	0.3m	RS-232	Prolific - PL2303GT	-
ICUSB232FTN	179-7985	USB-A	RS232	1	921.6kbit/s	USB 2.0	1.8m	RS-232	FTDI - FT232RL	-
ICUSB23216FD	186-4054	USB-A	RS232	16	921kbit/s	USB 2.0		RS-232	FTDI - FT232RL	Data Transmit, Data Receive
ICUSB232PROC	186-4052	USB-C	RS232	1	921.6kbit/s	USB-C	0.4m	RS-232	Prolific - PL2303GT	-
ICUSB2324I	179-7980	USB-A	RS232	4	921.6kbit/s	USB 2.0		RS-232	FTDI - FT4232HL	Rx, Tx
ICUSB2321F	123-8048	USB-A	RS232	1	115.2kbit/s	USB 2.0	1.8m	RS-232	FTDI - FT232RL	-
ICUSB1284	193-2833	USB-A	Centronics (36 pin)	1	-	USB 2.0	1.8m		Prolific - PL2305	-
ICUSB2321X	179-7983	USB-A	RS232	1	230.4kbit/s	USB 2.0	0.3m	RS-232	Texas Instruments - TIUSB3410	-
ICUSB2328	193-2837	USB-A	RS232	8	921.6kbit/s	USB 2.0	1.8m	RS-232	FTDI - FT232RL	-
ICUSB2324X	186-4055	USB-A	RS232	4	230.4kbit/s	USB 2.0		RS-232	Texas Instruments - TIUSB3410	-
ICUSB232DB25	123-8049	USB-A	RS232 has (DB9 to DB25 adapter)	1	230.4kbit/s	USB 2.0	0.9m	RS-232	Prolific - PL2303GC	-