

Datasheet
 Stock No:1707018
 RS Pro
 BNC STRAIGHT BULKHEAD JACK-JACK ADAPTER

NO	DESCRIPTION	DATE
A	13-29-14/R13-029-14-0026220AE → 40131201300028	02.02.18

MOUNTING HOLE
SCALE 2:1

APPROVED by _____ DATE: _____

DESCRIPTION	BNC STRAIGHT BULKHEAD JACK-JACK ADAPTER		
DRAWN	品名	40131201300028	DATE
Jackie	标题	VAROHS COMPLIANT (750)	日期
CHECK	UNIT		版次
A7c	mm(in)		A-1
APPROVAL	DWG. NO.	13-0691-Z	
Jenny	SCALE		
认定	比例	3:1	

7	INSULATION	TEFLON	1	NONE
6	INSULATION	TEFLON	1	NONE
5	CENTER CONTACT	BERYLLIUM COPPER	1	GOLD 3 μ MIN.
4	BODY	BRASS	1	NICKEL 100 μ MIN.
3	WASHER	BRASS	1	NICKEL
2	WASHER	STEEL	1	NICKEL
1	NUT	BRASS	1	NICKEL 100 μ MIN.
NO.	DESCRIPTION	MATERIAL	QTY	FINISH

1.0 ELECTRICAL

1.1 FREQUENCY RANGE: DC-6 GHz
 1.2 NOMINAL IMPEDANCE: 75 OHMS
 1.3 VOLTAGE RATING: 500 VOLTS MAX.
 1.4 VSWR: 1.2 MAX.

2.0 MATERIALS

2.1 BODIES: BRASS PER IIS-C9604
 2.2 CENTER CONTACT: BERYLLIUM COPPER PER ASTM B196 UNS C17300
 2.3 INSULATION: TEFLON PER ASTM D1457 AND ASTM D1710

3.0 FINISHES AND OTHERS

3.1 SEE BELOW TABLE FOR DETAILS.

4.0 MECHANICAL

4.1 INTERFACE IN ACCORDANCE WITH MIL-STD-348B

5.0 ENVIRONMENTAL

5.1 OPERATING TEMPERATURE RANGE: -65° C TO +165° C