

## FEATURES

- Ultra-flexible in low temperature environments
- Exceptional abrasion resistance
- Resistant to a wide range of chemicals
- Compliant with F&DA regulations
- Excellent clarity for clear visibility
- High levels of kink resistance and good memory
- 87 Shore A hardness

## RS PRO PUR Flexible Tubing, Transparent, 12mm External Diameter, 25m Long Reinforced, 70mm Bend Radius, Applications

RS Stock No.: 339-6281



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

### Product Description

This polyurethane hose features outstanding elasticity helping to provide excellent flexibility as well as having a high kink-resistance. Even in cold conditions, the reliable hose constriction remains durable, flexible and still highly kink-resistant. Resistant to a wide range of chemicals, the abrasion resistant clear hose provides excellent visibility to see blockages or issues within the hose.

### General Specifications

<b>Material</b>	PUR
<b>Colour</b>	Transparent
<b>Reinforced</b>	Yes
<b>Application</b>	Fuel, Gas, Granule, Liquid, Powder, Solvent, Conveyance of gases, Liquids and fluids, Dry powders and granules (especially where good abrasion characteristics are required)

### Mechanical Specifications

<b>Inner Diameter</b>	6.3mm
<b>Outer Diameter</b>	12mm
<b>Length</b>	25m
<b>Bend Radius</b>	70mm

### Operation Environment Specifications

<b>Minimum Operating Temperature</b>	-40°C
<b>Maximum Operating Temperature</b>	+65°C
<b>Maximum Working Pressure</b>	13 bar

## Approvals

Compliance/Certifications	ISO7751(1997) Polyurethane Hose
---------------------------	------------------------------------