E3032RJ5E_GS

2 Gang RJ45 8 Pin Data Outlet, Grey Silver





Main	
Product or component type	Data socket
Data socket type	RJ45 - 8 contacts - category 5e
Colour tint	Grey silver

Complementary

o impromornary		
Rated current	1.5 A	
Socket number	2	
Insulation resistance	>= 200 mOhm	
Contact resistance	1000 μOhm	
Number of gangs	2 gangs	
Minimum return loss	23 dB	
AWG gauge	AWG 26AWG 22 (4 twisted pair cables)	
Contacts material	Contact: phosphor bronze with gold plating IDC contact: phosphor bronze with nickel plating	
Material	Polycarbonate: plastic part	
Device mounting	Surface Flush	
Width	87 mm	
Height	87 mm	
Depth	36 mm	

Environment

Dielectric strength	1000 V for 60 s at 60 Hz
Ambient air temperature for operation	040 °C
Relative humidity	095 %
Environmental characteristic	Indoor use
Standards	EIA/TIA 568 FCC part 68 ISO/IEC 11801 YD/T 577-92

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.6 cm	
Package 1 Width	8.7 cm	
Package 1 Length	8.7 cm	
Package 1 Weight	92 g	
Unit Type of Package 2	BB1	
Number of Units in Package 2	8	
Package 2 Height	9.5 cm	

Package 2 Width	15 cm	
Package 2 Length	19 cm	
Package 2 Weight	750 g	
Unit Type of Package 3	CAR	
Number of Units in Package 3	80	
Package 3 Height	21 cm	
Package 3 Width	31 cm	
Package 3 Length	50 cm	
Package 3 Weight	8500 g	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	

Contractual warranty

Warranty 18 months	
--------------------	--