

Datasheet

RS PRO 2 Core Unscreened Industrial Cable, 0.34mm² 100m

Stock No: 195-9506




Technical Specifications:

Conductor	Stranded Bare Copper	Cabling	Yes
Cores Number	2C	Filler	—
Size(AWG)	22	Paper	—
Construction(±0.008mm)	7/0.25	Drain wire(AWG)	—
Stranded Dia.(mm)	0.75	Braiding shield	—
Insulation Material	PVC	Coverage(%)	—
Insulation Color	WH,BR	Jacket Material	PVC
Ave Thickness(mm)	0.38	Jacket Color	GY(RAL7000)
Min Thickness(mm)	0.33	Ave Thickness(mm)	0.76
Insulation Dia.(±0.05mm)	1.55	Min Thickness(mm)	0.61
Twist	—	Outer Dia(±0.20mm)	4.70
PET Mylar	—		

Features & Benefits:

- Operating temperature: $-5\text{ }^{\circ}\text{C} \rightarrow +80\text{ }^{\circ}\text{C}$
- Conductor resistance($20^{\circ}\text{C } \Omega/\text{km}$): 55 max.
- Operating voltage: 300 V
- Flammability Test: VW-1

Cross Section drawings



Cable Marking: E254881 UL AWM STYLE 2464 80°C
300V VW-1 cUL AWM I/II A 80°C 300V FT1 -LF- ELETECK

Reference Standard:

UL758

UL2464