

Dual Wall Tubing (4X)

Flexible, Outer Layer Flame Retardant, Heat Shrink

multicomp PRO

RoHS
Compliant



Description

This is made from flexible polyolefin and hot melt glue through high technology co-extrusion. The outer flexible polyolefin has low shrink temperature and the low shrink point glue so has the advantage for water proof and mechanical strain buffer performances. It is widely applied for automotive wiring harnesses water proof, gas leak and drain; Multi-strand and wire branch harness waterproof.

Specifications

Continuous Operating Temperature	: -45°C to +125°C
Full Recovery temperature	: 105°C
Minimum shrink temperature	: 60°C
Shrink Ratio	: 4:1
Colour	: Black
Resistant to UV	

Outer Layer - Technical Data

Property	Test Method	Typical Data
Tensile Strength	ASTM D 2671	≥10.4MPa
Elongation	ASTM D 2671	≥300%
Tensile Strength after aging	UL 224 158°C×168hrs	≥7.3MPa
Elongation After aging	UL 224 158°C×168hrs	≥100%
Longitudinal Change	ASTM D 2671	-8% to +8%
Flammability	SAE-AMS-DTL-23053/5	30s self-extinguish
Dielectric Strength	IEC 60243	≥15kV/mm
Volume Resistivity	IEC 60093	≥10 ¹⁴ Ω·cm

Adhesive - Technical Data

Property	Test Method	Typical Data
Water absorption ratio	ASTM-D570	≤0.2%
Softening point	ASTM-D E28	85°C
Peel Strength (PE)	ASTM-D1000	120N/25m
Peel Strength (AL)	ASTM-D1000	80N/25m

Dual Wall Tubing (4X)
Flexible, Outer Layer Flame Retardant, Heat Shrink



Product Dimensions

Part Number	Size		As supplied	After recovery(mm)		
	Inch	mm	Internal Diameter(mm)	Internal Diameter	Total Wall Thickness	Adhesive thickness
PP001978	5/32	4	≥4	≤0.95	1.2 ±0.2	0.5 ±0.2
PP001980	5/16	8	≥8	≤1.65	1.65 ±0.2	0.76 ±0.2
PP001977	1/2	12	≥12	≤2.41	2 ±0.2	1.02 ±0.2

Part Number Table

Description	Part Number
Tubing, Heat Shrink, Dual Wall, Flexible, 12mm, Black, 1.22m	PP001977
Tubing, Heat Shrink, Dual Wall, Flexible, 4mm, Black, 1.22m	PP001978
Tubing, Heat Shrink, Dual Wall, Flexible, 8mm, Black, 1.22m	PP001980

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
 Farnell.com/multicomp-pro
 sg.element14.com/b/multicomp-pro

