

## FEATURES

- Supports a wire size of 24AWG to 28AWG
- Suitable for crimping bootlace ferrules
- Ensures integrity the connector termination
- The indents are clearly marked with the different wire size ranges

## RS PRO Plier Crimping Tool for Crimp Contact

RS Stock No.: 210-5012



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

### Product Description

RS PRO crimp tool, designed for crimping crimp contacts. This professional tool offers wire range size of 24 AWG to 28 AWG with clear identifying marks on the head of the tool. A plier shape design and superb comfort in both hands deliver the perfect crimp every time.

### General Specifications

<b>Crimp Tool Type</b>	Plier
<b>Crimp Connector Type</b>	Crimp Contact
<b>Applications</b>	Crimping tools can be used for a variety of applications: Maintenance & repair, Electrical Installations, Computer Interfacing, Cable assemblies

### Mechanical Specifications

<b>Overall Length</b>	215 mm, 215.9 mm
<b>Wire Size (AWG)</b>	24 AWG, 26 AWG, 28 AWG

### Operation Environment Specifications

<b>Minimum Operating Temperature</b>	0°C
<b>Maximum Operating Temperature</b>	70°C
<b>Operating Temperature Range</b>	0°C to 70°C



Contacts:	
Headers/IDT Sockets	Tin Plated Brass
Sockets (crimp/PCB).	Tin Plated Phosphor Bronze
Insulation	Nylon rated 94V-0
	IDT Version UL94V-2
Max Voltage	250 V ac.
Max Current	2.5A per way
Operating Temperature	0°C to +70°C
Pin Size	0.64mm square
Recommended PCB Hole dia.	1.19mm ± 0.05mm