Eaton ABC-2-R

Catalog Number: ABC-2-R

Eaton ABC series Fast-acting fuse 2A, 250 Vac, 125 Vdc, 32 Vac (self certified), ABC-2-R



General specifications

| Product Name | Catalog Number |
|---------------------------------------|---|
| Eaton Bussmann series ABC fast-acting | ABC-2-R |
| fuse | UPC 051712646208 |
| Product Length/Depth | Product Height |
| 1.25 in | 0.25 in |
| Product Width | Product Weight |
| 0.25 in | 0.007 lb |
| Compliances | Catalog Notes |
| CE Marked | Ceramic body allows for higher amp/volt |
| RoHS Compliant | rating combinations. |



Product specifications

Fuse indicator

Non-indicating

Interrupt rating 100 AIC at 250 Vac 10 kAIC at 125 Vac/dc

Connection Ferrule end x ferrule end

Response time 4 hr at 100%, 60 min at 135%, 120 sec at 200%

Quantity

5

Material Ceramic tube Nickel-plated brass endcaps

Melting (I2T) Typical pre-arc: 2.167

Amperage Rating

2 A

Voltage drop 0.31 mV typical

Resistance 0.089 ohms DC cold

Туре

Electronic

Voltage rating 250 Vac, 125 Vdc, 32 Vac (self certified)

Application

Electronic circuits

Resources

PEP Eco-passport EATO-00033-V01.01-EN

Specifications and datasheets Eaton Specification Sheet - ABC-2-R

Eaton ABC fast-acting ceramic tube fuses data sheet



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2023 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia