


Valve-regulated lead acid (VRLA) battery with absorbed glass mat (AGM) technology provides high economic performance.

Suitable for various applications such as security system, emergency lighting and other general stand-by power applications.




BATTERY MODEL	TERMINAL	CASE MATERIAL
NE7-12	Faston 187 (F1) Faston 250 (F2)	ABS/UL94-HB
Nominal Voltage (V)		12
20-hr rate Capacity to 10.5V at 25°C (Ah)		7.0
10-hr rate Capacity to 10.5V at 25°C (Ah)		6.54
DIMENSIONS		
Length (mm)		151
Width (mm)		65
Height over terminals (mm)		100
Weight (kg)		1.95(±5.0%)
OPERATING TEMPERATURE RANGE		
Storage (in fully charged condition)		-15°C to + 40°C
Charge		-0°C to + 40°C
Discharge		-15°C to + 40°C
STORAGE		
Capacity loss per month at 25°C (% approx.)		3
*NE series batteries can be stored for up to six months at 25°C. During the storage, recharge the battery at least every six month.		
CHARGE VOLTAGE		
Float charge voltage at 25°C (V)/Battery		13.7-13.9
Float charge voltage temperature correction factor from standard 25°C (mV)/°C/Cell		-3
Cyclic (or Boost) charge voltage at 25°C (V)/Battery		14.6-14.8
Cyclic charge voltage temperature correction factor from standard 25°C (mV)/°C/Cell		-4
CHARGE CURRENT		
Maximum charge current (A)		2.1
DISCHARGE CURRENT		
Maximum continuous discharge current, 5 sec. (A)		72
Short circuit current (A)		360
IMPEDANCE		
Measured at 1 kHz (mΩ)		35
DESIGN LIFE		
YUVOLT design life at 25°C		up to 3 years

CHARGE CHARACTERISTICS




CHARGE VOLTAGE


Relationship Between Temp and Charge Voltage




FLOAT SERVICE LIFE



TERMINALS



DIMENSIONS



*Please do not use this product for medical devices or medical purposes. It is not designed for these usages.

GS Yuasa International, Ltd.
Overseas Sales Department
Power Supply System Sales Division
Industrial Batteries & Power Sources Business Unit

1-7-13, Shiba-koen, Minato-ku,
Tokyo 105-0011, Japan

Please contact to shunsuke.kohmoto@jp.gs-yuasa.com