

Data sheet

PT

RS Stock No.324-2666

ENGLISH



TYPE K SHEATH THERMOCOUPLE											
RANGE :											
•											
USE :											
• Plastic factory											
KEY POINT :											
•											
SPECIFICATIONS :											
<ul style="list-style-type: none"> • Hot junction ungrounded • 316L ss mineral insulated Ø1.5 • Undismontable transition Ø5 x 35 mm metallic transition • MgO insulation • Insulated conductor and Armour in Fiber glass • External insulation in stainless steel braid 											
DIMENSIONS :											
<ul style="list-style-type: none"> • Cable Length = 2000 • Length =500 											
METROLOGICAL DATA :											
<ul style="list-style-type: none"> • As per IEC 584 • <u>Standard tolerance TC "K" class1:</u> -40°C < t° < 375°C = ± 1.5°C 375°C < t° < 1000°C= ±0.004. [t] • Time constant at 63% in water: 0.7 sec • Output signal FEM(mV) as per curve of "K" type as per norme IEC 60584 											
<u>Other Dimensions :</u>											
<table border="1"> <tr> <td style="text-align: center;">Length</td> <td style="text-align: center;">250</td> <td style="text-align: center;">500</td> </tr> <tr> <td style="text-align: center;">Diameter</td> <td style="text-align: center;">334-2650</td> <td style="text-align: center;">324-2666</td> </tr> <tr> <td style="text-align: center;">1,5</td> <td></td> <td></td> </tr> </table>			Length	250	500	Diameter	334-2650	324-2666	1,5		
Length	250	500									
Diameter	334-2650	324-2666									
1,5											