

RoHS  
Compliant



## Applications

- Indicated for floor marking of sport courts, factories, offices, banks, mails, parking lots.
- It can also be used for marking clear and smoked glass, as well as identifying industrial facilities (oil, water, and other products pipes).
- Used for decorating and protecting.

## Specifications

Total Thickness	: 0.15mm
Adhesion	: >1.5 N/CM
Adhesion to Steel	: >1 N/M
Tensile Strength	: >18 N/CM
Elongation	: >150%
Heat Resistance	: -12°C to +80°C
Width	: 50mm
Length	: 33m

## Storage and Shelf Life

Clean and dry in a well ventilated area, preferably at a temperature between 10°C and 30°C. Stored under these conditions shelf life will be 12 months.

## Usage

Temperature: between 0°C and + 50°C. Surface must be clean and free from dust and grease. Avoid touching the tapes exposed adhesive surface in order to keep full adhesive performance. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 HRS at 23°C.

## Part Number Table

Description	Part Number
Hazard Warning Tape, PVC, 50mm×33m, Black/Yellow	SH5012-B/Y

**Important Notice** : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands  
Farnell.com/exclusive-brands  
Element14.com/exclusive-brands