### **Anti-Vandal Switches Push Button**

## multicomp PRO









RoHS **Compliant** 

#### **Specifications**

#### Material

: Zinc Alloy, Nickel Plated Bushing

**Bushing Colour** : Black Base : PA

Contact : Silver alloy, (2mm × 0.5mm)

Button : PBT

#### **Electrical**

Switch Rating : 2A @ 36V DC Contact Resistance :  $50m\Omega$  max. initial Insulation Resistance :  $1000M\Omega$  min. : 1500V AC Dielectric withstanding voltage

Electrical Life : 200,000 cycles min.

#### Mechanical

Operating Force : 3.5N

**Nut Torque** : 0.3Nm max.


#### **Temperature Rating**


Operating temperature : -25°C to +55°C


#### **Environmental**


Front Panel Protection : IP65

#### Diagram









Seal Ring

Dimensions: Millimetres

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro

multicomp PRO

# Anti-Vandal Switches Push Button



#### **Part Number Table**

Description	Button Colour	Part Number
Anti Vandal Switch, SPST, Off-MOM, Raised	Yellow	MP-PB7-01PB4EBRYM
	Blue	MP-PB7-01PB4EBRBM
	Red	MP-PB7-01PB4EBRRM
	Green	MP-PB7-01PB4EBRGM

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro

