

Datasheet

## RS Pro Crimp Ring Terminal, M5 Stud Size, 0.2mm<sup>2</sup> to 0.5mm<sup>2</sup>, 26AWG to 22AWG

RS Stock No: **239-4149**



### Product Details

RS Pro crimp ring terminal has M5 stud size. It suits cables from 0.2 mm<sup>2</sup> to 0.5 mm<sup>2</sup> and 26 AWG to 22 AWG. A range of insulated crimp ring terminals made from copper with flared vinyl or nylon (mini yellow) insulation. These insulated crimp ring wire connectors are colour coded for use with different wire sizes including mini yellow 0.2 - 0.5 mm<sup>2</sup> and are available with a variety of stud sizes.

**Specifications:**

Colour	Yellow
Contact Material	Copper
Contact Plating	Tin
Inner Ring Diameter	5.3 mm
Insulation Material	Nylon
Insulation	Insulated
Maximum Wire Size (AWG)	22 AWG
Maximum Wire Size (mm <sup>2</sup> )	0.5 mm <sup>2</sup>
Minimum Wire Size (AWG)	26 AWG
Minimum Wire Size (mm <sup>2</sup> )	0.2 mm <sup>2</sup>
Outer Ring Diameter	8 mm
Overall Length	20 mm
Stud Size	#10
Wire Size	26 to 22 AWG
Temperature Rating	+105°C
Amperage Rating	5.5 to 9 A
Voltage Rating	600 V
Type	Single Crimp