

Main

Range	ComPacT
Range of product	ComPacT NS630b1600 new generation ComPacT NS1600b3200 new generation
Device short name	MX
Product or component type	Voltage release
Device application	Control
Voltage release type	Opening coil Instantaneous voltage release
Control type	Standard
[Uc] control circuit voltage	200250 V AC 50/60 Hz 200250 V DC
Circuit breaker mounting mode	Fixed
Range compatibility	ComPact (ComPact NS630b1600) ComPact (ComPact NS1600b3200)

Complementary

Operating threshold	0.71.1 x Un opening
Response time	50 ms +/- 10 % for Compact NS630b1600
	50 ms +/- 10 % for Compact NS1600b3200
	55 ms +/- 10 % for MasterPact NT
	70 ms +/- 10 % for MasterPact NW
Supply holding power	4.5 VA
Accessory / separate part category	Spare part for MasterPact NT
	Spare part for MasterPact NW
	Spare part for ComPacT NS630b1600 new generation
	Spare part for ComPacT NS1600b3200 new generation

Packing Units

racking office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.3 cm
Package 1 Width	6.0 cm
Package 1 Length	8.2 cm
Package 1 Weight	150.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9.0 cm
Package 2 Width	13.2 cm
Package 2 Length	18.5 cm
Package 2 Weight	1.556 kg
Unit Type of Package 3	S03
Number of Units in Package 3	120
Package 3 Height	30.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	19.303 kg

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEL RoHS Declaration
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Contractual warranty

	Warranty	18 months
--	----------	-----------