

HB 8010P (Tesa PE Foam)

FEATURES

HB 8010P

Roll dimensions 19mm x 50m

White 1mm thick Polyethylene Foam tape double -sided coated with a high grade acrylic pressure sensitive adhesive. Closed cell 67kg/m3 PE Foam carrier.

For general purpose bonding , fixing and mounting applications, suitable for external and

Internal applications, the tape acts as a fixing and sealing product with dust, water and moisture sealing properties. The tape gives good vibration dampening and anti-rattle properties.

Applications:

Uses in the sign industry, bonding profiles and ducting, mirror mounting,

Applications in the window and door market (wood, PVC and aluminium)

Fixing in the point of sales and display industries. Fixing hooks hangers andshelf talkers.

RS PRO Polyethylene Double Sided Mounting tape

RS Stock No: 224-3440



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has



been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

Product description

- Double sided closed cell polyethylene foam
- High quality solvent acrylic pressure sensitive cross-linked adhesive
- Excellent bonding properties for low surface tension substrates
- Good moisture and humidity resistance

Construction

- White paper liner (80μm)
- Acrylic adhesive
- White closed cell PE foam (1mm)
- Acrylic adhesive



- 1. Paper liner
- 2. Acrylic adhesive coating
- 3. White closed cell PE foam
- 4. Acrylic adhesive coating

This tape has a shelf life of 1 year when store at an ambient temperature of 15-25 °C

General Specifications

| Item | Unit | | Spec. | | Test method |
|------------------------|--------|--------|---------|---------|-------------|
| Foam thickness | mm | In | 1 | .0394 | - |
| Foam Density | kg/m³ | lb/ft³ | 67 | 4.37 | - |
| 180° Peel adhesion | N/25mm | - | 27 | - | - |
| Dynamic shear | N/cm² | - | 75 | - | - |
| Static shear | kg/cm² | - | 0.8 | - | - |
| Temperature resistance | °C | °F | -40~120 | -40~248 | - |

Approvals

| Declarations | |
|---------------|--|
| Standards Met | |

Similar Products

| Stock No. | Brand | Product Name | Colour | Material |
|-----------|-------|--------------|--------|----------|
| | | | | |

