



PIG® Ceiling Tile Leak Diverter

TLS366 Ceiling Tiles, Diverter Only, 2' x 2'

Leak diversion system replaces damaged ceiling tile for discrete channeling of liquids until you find and fix the leak.

- Remove damaged tile and replace it with a leak diverter panel to channel away liquids
- Minimizes wet floors, damaged equipment and disturbances to workers
- Captures leaks and drips and diverts them to a drain or storage tank with included 25'L hose
- Clips let you secure hose to ceiling grids for a professional appearance
- Flow rate of 0.2 gallons per minute when used with included hose
- After leak has been repaired, simply uninstall and store for later use
- Replaces any standard 2' x 2' drop ceiling tile

Specifications

Style	Diverter Only
Color	White
Dimensions	2' W x 2' L
Drainage Hose Included	Yes
Hanging Straps Included	No
Hose Connector	.5"
Installation Method	Ceiling Clips
Shape	Square
Sold as	1 each
Weight	6 lbs.
# per Pallet	80
Composition	Diverter - Polystyrene Hose - Vinyl Clips - Plastic
Application	Ceiling Tiles
Flow Rate	0.2 gal./Minute
Includes	1 - 2' L x 2' W Leak Diverter 1 - 25' L Drainage Hose 6 - Ceiling Clips

UNSPSC	24141506
Pigalog® Page Number	Page 265

Metric Equivalent

Dimensions	61cm W x 61cm L

Weight 2.7 kg

Technical Information

Technical Documents

Instructions for PIG Drop-Ceiling Leak Diversion System

Disclaimers

Maximum Working Temperature

Not suitable for temperatures over 170°F/77°C.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447• newpig.com • hothogs@newpig.com