



Main

Range	Kavacha
Product or component type	Socket-outlet
Device short name	AS
Device application	Power supply
Colour tint	White
Colour tint (Frame)	White

Complementary

Wiring device mounting	Surface
Rated current	13 A at 250 V AC
Number of gangs	1 gang
Width	80 mm
Height	117 mm
Depth	80 mm

Environment

IP degree of protection	IP56
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.3 cm
Package 1 Width	8.5 cm
Package 1 Length	12 cm
Package 1 Weight	272.727 g
Unit Type of Package 2	CAR
Number of Units in Package 2	45
Package 2 Height	27.8 cm
Package 2 Width	36 cm
Package 2 Length	47 cm
Package 2 Weight	12000 g
Unit Type of Package 3	P12
Number of Units in Package 3	900
Package 3 Height	80 cm
Package 3 Width	105 cm
Package 3 Length	120 cm
Package 3 Weight	245 kg

Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.