



Plusline Small

Plusline S 500W R7s 240V 1CT/10X10F

Mains-voltage linear lamp giving white halogen light

Product data

General information	
Cap-Base	R7S [R7s]
Operating Position	UNIVERSAL [Any or Universal (U)]
Nominal Lifetime (Nom)	2000 h
Rated Lifetime (Hours)	2000 h
Rated Lifetime (Years)	2 a
Light technical	
Luminous Flux (Nom)	9660 lm
Correlated Color Temperature (Nom)	2900 K
Luminous Efficacy (rated) (Nom)	19.3 lm/W
Color Rendering Index (Nom)	100
Operating and electrical	
Power (Nom)	500 W
Lamp Current (Nom)	2.08 A
Starting Time (Nom)	0.0 s
Voltage (Nom)	240 V
Controls and dimming	
Dimmable	Yes

Mechanical and housing	
Bulb Finish	Clear
Bulb Shape	T3 [T 12mm (T3)]
Luminaire design requirements	
Bulb Temperature (Max)	900 °C
Pinch Temperature (Max)	350 °C
Pinch Temperature (Max)-DUP(do not use)	350 °C

Product data	
Full product code	872790080905300
Order product name	Plusline S 500W R7s 240V 1CT/10X10F
EAN/UPC - Product	8727900809053
Order code	924735545579
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	100
Material Nr. (12NC)	924735545579
Net Weight (Piece)	0.010 kg
ILCOS Code	HDG//RS-500-240-R7s-114,2

Plusline Small

Dimensional drawing



Product	D (max)	B (max)	B	B (min)	C (max)
Plusline S 500W R7s 240V 1CT/10X10F	12 mm	115.8 mm	114.2 mm	112.6 mm	117.6 mm

Plusline S 500W R7s 240V 1CT/10X10F

