

IMPACT PROTECTION. HIGH CUT RESISTANCE.



EN388:2016 STANDARDS							
Abrasion	0	1	2	3	4	-	-
Cut Resistance (Coup Test)	0	1	2	3	4	5	Х*
Tearing	0	1	2	3	4	-	-
Puncture	0	1	2	3	4	-	-
Cut Resistance (TDM Test)	Α	В	С	D	E	F	Χ
Impact	Χ	Р	-	-	-	-	-

*If the coup test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead



SPECIFICATIONS				
Gauge	13			
Liner Material	Nylon and HPPE Blend Knit			
Dip Material	Sandy Nitrile			
TPR	PVC			
Cuff Style	Velcro Cuff			
Sizes	8, 9, 10, 11			

RECOMMENDED APPLICATIONS

- Back-of-Hand Protection
- Metal Handling
- Abrasive/Sharp Materials
- Oily & Wet Conditions
- Pipe Threading
- Cutting
- Glass Handling
- Duct Work

CARE INSTRUCTIONS

Machine wash warm water (105°F), mild detergent, no bleach. Line dry.

PACKING DETA	ILS
Selling Unit	1 Pair
Inner Pack	12 Pairs
Outer Carton	120 Pairs
Carton Size	66CM x 33CM x 44CM
Volume	0.0958CBM
Gross Weight	24KG



