

Robust power packs

The new LX series

- Chassis made from robust steel pipe frame
- Integrated trolley takes rough ground in its stride
- Large wheels with wide solid rubber tyres
- Integrated impact protection
- Electrical control box, protected by stainless steel cover
- Overheat protection
- Special electric motor for operation with 16 A fuse
- Thermal overload switches
- Eccentric parking brake
- Hose drum with 20 m
- Steel braided high-pressure hose, NW 10
- Lance, gun and hose equipped with coupling system

NEW!



Fig. LX series with hose drum



Technical specifications	LX 2000	LX 2500
Ord. no. with hose drum	40,830	40,840
Operating pressure, continuously adjustable	30-150 bar (3-15 MPa)	30-130 bar (3-13 MPa)
Max. admissible overpressure	175 bar (17.5 MPa)	150 bar (15 MPa)
Water output	32 l/min (1,920 l/h)	41,5 l/min (2,490 l/h)
Motor speed	1,400 rpm	1,400 rpm
Connected load	400 V, 14 A, 50 Hz	400 V, 14 A, 50 Hz
Power intake / power output	9.6 kW / 7.8 kW	9.6 kW / 7.8 kW
Weight without accessories	125 kg	125 kg
Features & Equipment		
Steel braided high-pressure hose, NW 10	20 m (47,7021)	20 m (47,7021)
Trigger gun with safety catch and quick-action coupling	Starlet (12,3273)	Starlet (12,3273)
Stainless steel lance with flat jet nozzle and plug-in nipple	(12,420-D40125)	(12,420-D40175)
Turbokiller with stainless steel lance 1000 mm, with recessed handles and plug-in nipple (optional)	(12,430-12)	(12,430-18)