

Datasheet

Stock No: 240-113

ENGLISH

RS Pro High Power Series Metal Oxide Varistor 3.085nF



Product Details

Metal Oxide Varistors High Power

High power metal oxide varistors suitable for reducing transient voltage spikes in industrial power applications.

Single and two-hole fixing types for distribution bus-bar mounting Insulated plastic case types for flat surface mounting

High-mass large-diameter zinc oxide element

Repeatable protection against high-energy transient voltages

Operating Temperature Range: -40°C → +85°C

Transient Voltage Suppressors (MOV)



ENGLISH

Product Details

| Dimensions (mm) | | | | | | |
|--------------------|----|----|----|------------------|----------------|--|
| Package Type | L | W | Н | Fixing Hole Dia. | Fixing Centres | |
| Radial disc, Ø40 | 66 | 40 | 22 | 6.35 | _ | |
| Radial disc, Ø34 | 65 | 24 | 20 | 5.5 | 52 | |
| Encapsulated block | 61 | 50 | 40 | 5.4 | 51 | |

Specifications:

| Varistor Voltage | 360V |
|---------------------------|---------------|
| Maximum AC Voltage Rating | 250V |
| Maximum DC Voltage Rating | 330V |
| Clamping Voltage | 620V |
| Energy | 190J |
| Series | High Power |
| Diameter | 36mm |
| Maximum Surge Current | 12000A |
| Capacitance | 3.085nF |
| Thickness | 4mm |
| Dimensions | 36 Dia. x 4mm |