

RoHS Compliant



Description

These series is fast-acting, high breaking capacity fuse.

Features

- Fast-Acting, high breaking capacity under 500V AC/DC.
- Φ6mm × 32mm physical size
- · Special engineering material tube, Silver plated copper cap construction.
- · High breaking capacity for high energy application.

Specifications


Operating Temperature : -55°C to 125°C Storage Conditions : +10°C to +60°C

Relative humidity : \leq 75% yearly average without dew, maximum 30 days at 95% Vibration Resistance : 24 cycles at 15 min. each (60068-6) 10-60Hz at 0.75mm amplitude

60-2000Hz at 10g acceleration

Construction And Mechanical Characteristics

Dimensions



Dimensions : Millimetres

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro





Electrical characteristics

Electrical Characteristics at 25°C								
Amp Code	Rated Current	Rated Voltage	Breaking Capacity	Typical Voltage Drop(mV)	Typical Cold Resistance (mΩ)	Typical Melting I²T (A²s)		
MP013399	10A	500V AC 500V DC	1KA @ 500V AC 1KA @ 500V DC	265	17.1	100		
MP013400	12A			220	12.3	140		
MP013401	15A			185	8	66		
MP013402	16A			190	8	62		
MP013403	20A				5.65	125		
MP013404	25A				4.35	270		
MP013405	30A			205	3.5	450		

Notes: (1) DC cold resistance are measured at <10% of rated current in ambient temperature of 25°C.

(2) Typical pre-arcing I2t are measured at 10In current.

Electrical Specifications


Time vs Current Characteristics Table

(measured with constant current power supply)

Rated Current	200	300	
10A~30A	<5min	<10s	




Average Time Current (I-T) Curves





Temperature Derating Curve



Part Number Table

Description	Part Number
Cartridge Fuse, 10A, 500V AC/DC, Lead Free	MP013399
Cartridge Fuse, 12A, 500V AC/DC, Lead Free	MP013400
Cartridge Fuse, 15A, 500V AC/DC, Lead Free	MP013401
Cartridge Fuse, 16A, 500V AC/DC, Lead Free	MP013402
Cartridge Fuse, 20A, 500V AC/DC, Lead Free	MP013403
Cartridge Fuse, 25A, 500V AC/DC, Lead Free	MP013404
Cartridge Fuse, 30A, 500V AC/DC, Lead Free	MP013405

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro

