
Stêrenê

AUTOCLAVABLE GOGGLES

Description

Autoclavable goggles with premium anti-fog lens. For use in cleanrooms and sterile/critical areas.





Notes: Dimensions in mm

TEST DATA SUMMARY

| Parameter | Results | Remarks |
|---|---------------|------------------------|
| Refractive Power (Mounted and unmounted oculars covering both eyes) | PASS | Optical Class 1 |
| Quality of Material and surface | PASS | |
| Increased Robustness (Type: Goggle) | PASS (55±2'C) | 5.1m/s 22mm 43g |
| | PASS (-5±2'C) | Drop Ba ll 1.3m |
| Stability at elevated temperature | PASS | |
| Protection against optical radiation | VLT: 88-90% | UV 295 nm |
| Protection against high-speed particles. (Type: Goggle) | PASS | Medium Energy |
| | | impact (B) 120m/s |
| | | ~400fps 6mm dia |
| | | ball of 0.86g |
| Resistance to fogging of oculars | PASS | "N" marking req't: |
| | | ≥8 (s) |

Tested to withstand 40 cycles of autoclave in steam (at 121°C, 110kPa, 30 minutes)**

^{**}tested under laboratory conditions using only DI water to clean the lens

| Part no. | Dimensions | Packaging |
|-----------|------------|---------------------------|
| GGL500-AF | 21cm x 9cm | 1 piece/bag, 50 bags/case |