Rocker Switches

multicomp PRO

RoHS

Compliant



Specifications

Material Movable Contact

Terminals Cap Actuator

Electrical

Rating

Contact Resistance Insulation Resistance Dielectric withstanding Voltage Electrical Life

Temperature Rating Operating temperature


Environmental IP Class : Copper Alloy, Silver Plated
: Silver Plated with outer layer in gold plating
: Plastic, Color Black

: 5 Amps with resistive load @ 125V AC or 28V DC 2 Amps with resistive load @ 250V AC


- : 10mΩ max. initial
- : 1000MΩ min.
- : 1500V RMS @ sea level
- : 50,000 make and break cycles at full load


: -30°C to +85°C


: IP67



Dimensions : Millimetres







SWITCH MARKINGS



Part Number Table

Description	Part Number
Rocker Switch, DPDT, On-On, Solder type	MP-R2-4B-A-5-11

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro



Diagram