

Eaton ABC-30-R

Catalog Number: ABC-30-R

Eaton ABC series Fast-acting fuse 30A, 250 Vac, 125 Vdc, 32 Vac (self certified), ABC-30-R



General specifications

Product Name	Catalog Number
Eaton Bussmann series ABC fast-acting fuse	ABC-30-R
	UPC
	051712542487
EAN	Product Length/Depth
5027590226493	1.25 in
Product Height	Product Width
0.25 in	0.25 in
Product Weight	Compliances
0.008 lb	RoHS Compliant
	CE Marked

Catalog Notes

Ceramic body allows for higher amp/volt rating combinations.

Product specifications

Fuse indicator

Non-indicating

Interrupt rating

1000 AIC at 125 Vac

400 AIC at 125 Vdc

1 kAIC at 75 Vdc

200 AIC at 250 Vac

Connection

Ferrule end x ferrule end

Response time

4 hr at 100%, 60 min at 135%, 120 sec at 200%

Quantity

5

Material

Nickel-plated brass endcaps

Ceramic tube

Melting (I₂T)

Typical pre-arc: 1429

Amperage Rating

30 A

Voltage drop

0.09 mV typical

Resistance

0.002225 ohms DC cold

Type

Electronic

Voltage rating

250 Vac, 125 Vdc, 32 Vac (self certified)

Application

Electronic circuits

Resources

PEP Eco-passport

[EATO-00033-V01.01-EN](#)

Specifications and datasheets

[Eaton ABC fast-acting ceramic tube fuses data sheet](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)