



Datasheet

Stock No: 811-4387

ENGLISH

RS Pro BASEC 4 Core White Unscreened 3184Y Solid PVC Power Cable H05VV-F, 0.75 mm² CSA 6 A, 300 V, 500 V



Product Details

BASEC approved H05VVF/3183Y 3 Core Cable

Flexible, 3 core cable with fine stranded copper conductors.

Features and Benefits

- PVC sheath
- PVC insulation

Applications

- Household applications
- Covered, dry, steamed and humid areas where low mechanical stress exists

Flexible PVC Cable

Specifications:

Number of Cores	3
Cross Sectional Area	2.5 mm ²
Sheath Colour	Grey
Current Rating	20 A
Voltage Rating	300 V, 500 V
Outer Diameter	11.4mm
Sheath Material	Polyvinyl Chloride PVC
Harmonised Code	H05VV-F
Type	3183Y
Minimum Operating Temperature	-15°C
Maximum Operating Temperature	+70°C
Screened/Unscreened	Unscreened
Conductor Strand Type	Solid
American Wire Gauge	13 AWG
Size of Strands	0.25 mm
Core Strands	50/0.25 mm
Conductor Resistance	7.98 Ω/km
Number of Strands	50
Standards Met	BASEC
Conductor Material	Copper
Insulation Material	PVC Type TI1 to BS7655