



### Main

Range	Compact
Poles description	4P
Network type	AC DC
Network frequency	50/60 Hz
[Ie] rated operational current	DC-23A : 40 A DC 250 V 4 poles in series DC-23A : 40 A DC 125 V 2 poles in series DC-22A : 40 A DC 250 V 4 poles in series DC-22A : 40 A DC 125 V 2 poles in series AC-23A : 40 A AC 50/60 Hz 480 V NEMA AC-23A : 40 A AC 50/60 Hz 440/480 V AC-23A : 40 A AC 50/60 Hz 380/415 V AC-23A : 40 A AC 50/60 Hz 220/240 V AC-23A : 32 A AC 50/60 Hz 500 V AC-22A : 40 A AC 50/60 Hz 500 V AC-22A : 40 A AC 50/60 Hz 480 V NEMA AC-22A : 40 A AC 50/60 Hz 440/480 V AC-22A : 40 A AC 50/60 Hz 380/415 V AC-22A : 40 A AC 50/60 Hz 220/240 V
[Ui] rated insulation voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	40 A ( 60 °C )
[Icm] rated short-circuit making capacity	75 kA 500 V AC 50/60 Hz with upstream protection circuit breaker 15 kA 500 V AC 50/60 Hz switch-disconnector alone
[Ue] rated operational voltage	500 V AC 50/60 Hz 250 V DC
Suitability for isolation	Yes
Contact position indicator	Yes
Visible break	No
Pollution degree	3

### Complementary

Control type	Rotary handle
Handle colour	Black
Mounting mode	Fixed
Mounting support	DIN rail Plate
Upside connection	Front
Downside connection	Front
Cable cross section	1.5...50 mm <sup>2</sup>
Maximum power	AC-23: 230 V NEMA AC 50/60 Hz AC-23: 480 V NEMA AC 50/60 Hz AC-23: 440 V AC 50/60 Hz AC-23: 380/415 V AC 50/60 Hz AC-23: 500/525 V AC 50/60 Hz AC-23: 220/240 V AC 50/60 Hz
Rated duty	Uninterrupted
Intermittent duty class	Class 120 - 60 %
Enclosure dimensions for lthe	190 mm x 115 mm x 55 mm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

[I <sub>cw</sub> ] rated short-time withstand current	5.5 kA ( 30 s ) conforming to IEC 60947-3 3 kA ( 1 s ) conforming to IEC 60947-3 1.73 kA ( 3 s ) conforming to IEC 60947-3 0.067 kA ( 20 s ) conforming to IEC 60947-3
Mechanical durability	20000 cycles
Electrical durability	DC-23A : 1500 cycles 250 V DC 4 poles in series DC-22A : 1500 cycles 250 V DC 4 poles in series AC-23A : 1500 cycles 500 V AC 50/60 Hz AC-23A : 1500 cycles 440 V AC 50/60 Hz AC-23A : 1500 cycles 380/415 V AC 50/60 Hz AC-23A : 1500 cycles 220/240 V AC 50/60 Hz AC-22A : 1500 cycles 500 V AC 50/60 Hz AC-22A : 1500 cycles 440 V AC 50/60 Hz AC-22A : 1500 cycles 380/415 V AC 50/60 Hz AC-22A : 1500 cycles 220/240 V AC 50/60 Hz
Connection pitch	18 mm
Height	85 mm
Width	90 mm
Depth	62.5 mm
Product weight	0.6 kg

## Environment

Standards	IEC 60947-1 IEC 60947-3
Product certifications	CCC KEMA-KEUR
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C