



ENGLISH

Datasheet

Manual Hose Reel

With male swivel fitting and guard



Article No	Hose ID (mm / inch)	Hose Length (Outlet)	Lead Hose length (Inlet)	Working Pressure (bar / psi)	Fitting Thread Size (Inlet + Outlet)	Weight (N.W)
873-8851	9.5 / 3/8	30M	110cm	15 / 200	3/8 + 3/8	8 kgs
873-8854	8 / 5/6	30M	110cm	15 / 200	1/4 + 1/4	6.5 kgs
873-8857	9.5 / 3/8	25M	110cm	15 / 200	3/8 + 3/8	7 kgs
873-8860	10 / 3/8	20M	110cm	15 / 200	3/8 + 3/8	6.5 kgs

Works with suitable pneumatic tools

Used for Construction work areas, manufacturing facilities, automatic maintenance, home DIY etc..

Specification:

Reinforced Polyurethane Hose - ETHER Base

Hose Colour: Blue

Temperature Range: -40°C to +60°C

Product Descriptions:

- Open Type Hose Reel with hand Crank
- Heavy Duty Reinforced Steel Construction with Power Paint Coating
- ETHER Reinforced Polyurethane Hose:
 - ★ Great flexibility and user friendliness, even in sub-zero temperatures.
 - ★ Resistant to attacks from moisture and fungus.
 - ★ RoHS requirement and Silicon-free
- 360° Rotary Base for Easy Use
- 4pcs rubber stoppers to hold the reel in place when in use
- Includes mounting bracket and hardware for wall mounting
- Easy to mount and dismount from the wall for outdoor use
- Easily stored away

