

FEATURES

- Available in 25m length
- A voltage rating of 600/1000V
- Single core cable design
- Maximum operating temperature of 70°C

RS PRO Green/Yellow Single Core x 16.0sqmm (Class 5 PCW), PVC Insulated, 600/1000V, Type BK

RS Stock No.: 516-8050



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



Product Description

From RS PRO, comes a range of high quality and great value Tri-rated cables. Manufactured with a premium annealed copper conductor and insulated with PVC (Polyvinyl Chloride), these Tri-rated cables are a fantastic solution for use in control panels and other types of electrical equipment

General Specifications

| Туре | ВК |
|----------------|--|
| Tri-rated | Yes |
| Sheath Colour | Yellow/Green |
| Fire Behaviour | Flame Retardant |
| Application | Electrical cabinets, Industrial electrical installations, Small electronic devices, Relay and instrumentation panels, Control metering, Motor starters |

Electrical Specifications

| Voltage Rating | 600/1000V |
|----------------------|---|
| Current Rating | 95A |
| Conductor Material | 115/0.40mm Plain Annealed Copper (Class 5 to IEC 60228) |
| Insulation Material | PVC (Type TI1 to BS EN 50363) |
| Conductor Resistance | 1.21 Ω/km @ 20°C (Maximum) |

Mechanical Specifications

| Length | 25m |
|---------------------------|-------------------|
| Cross Sectional Area | 16mm ² |
| Outer Diameter | 7.2mm |
| American Wire Gauge | 7AWG |
| Core Strands | 126/0.4mm |
| Size of Strands | 0.4mm |
| Insulation Wall Thickness | 1.00mm (Nominal) |



| Operation Environment Specifications | |
|--------------------------------------|----------------|
| Operating Temperature Range | -15°C to 70°C |
| Minimum Operating Temperature | -15°C |
| Maximum Operating Temperature | 70°C |
| Approvals | |
| Standards Met | ÓÙÂ GHFIGEEÎ Á |