





EDS Factory Sealed Tumbler Switches

Explosionproof, Dust-Ignitionproof

Malleable Iron Body and Cover. Furnished with Internal Ground Screw.

NEC/CEC:

Class I, Division 1, Groups B⁺, C, D
 Class I, Division 2, Groups B, C, D
 Class II, Division 1 and 2, Groups E, F, G
 Class III
 NEMA 3, 7CD, 9EFG

	Hub Size (Inches)	Switch	Dead-End	Catalog Number ①	Feed-Thru
1-Gang — Front Operated					
20 Amp — 120-277 Vac ②					
 Dead-End	1/2	1-Pole	EDS150-F1	EDSC150-F1	
	1/2	2-Pole	EDS150-F2	EDSC150-F2	
	1/2	3-Way	EDS150-F3W	EDSC150-F3W	
	1/2	4-Way	EDS150-F4W ④	EDSC150-F4W ④	
 Feed-Thru	3/4	1-Pole	EDS175-F1	EDSC175-F1	
	3/4	2-Pole	EDS175-F2	EDSC175-F2	
	3/4	3-Way	EDS175-F3W	EDSC175F3W	
	3/4	4-Way	EDS175-F4W ④	EDSC175F4W ④	
30 Amp — 120-277 Vac ③					
	3/4	1-Pole	EDS175-F13 ④	EDSC175-F13 ④	
	3/4	2-Pole	EDS175-F23 ④	EDSC175-F23 ④	
	3/4	3-Way	EDS175-F3W3 ④	EDSC175-F3W3 ④	
	1	1-Pole	EDS110-F13 ④	EDSC110-F13 ④	
	1	2-Pole	EDS110-F23 ④	EDSC110-F23 ④	
	1	3-Way	EDS110-F3W3 ④	EDSC110-F3W3 ④	
2-Gang — Front Operated					
20 Amp — 120-277 Vac ②					
 Dead-End	1/2	1-Pole	EDS250-F1	EDSC250-F1	
	1/2	2-Pole	—	EDSC250-F2	
	1/2	3-Way	—	EDSC250-F3W	
	1/2	4-Way	—	EDSC250-F4W ④	
 Feed-Thru	3/4	1-Pole	EDS275-F1	EDSC275-F1	
	3/4	2-Pole	—	EDSC275-F2	
	3/4	3-Way	EDS275-F3W	EDSC275-F3W	
	3/4	4-Way	—	EDSC275-F4W ④	
	1	1-Pole	EDS210-F1	EDSC210-F1	
	1	2-Pole	EDS210-F2	EDSC210-F2	
	1	3-Way	EDS210-F3W	EDSC210-F3W	
	1	4-Way	EDS210-F4W ④	EDSC210-F4W ④	

① For aluminum backbox and cover, add suffix -A.
 ② 20 Amp — 1 HP at 120 Vac and 2 HP at 240 Vac.
 ③ 30 Amp — 2 HP at 120 Vac or 240 Vac.
 ④ Contains standard switch and sealing chamber.

◆ Shaded area indicates items suitable for Class I, Group B, as well as Class I, Groups C and D; Class II, Groups E, F, G; and Class III.

Appleton

CONTROLS: NEC/CEC EXPLOSIONPROOF CONTROL STATIONS AND SWITCHES