

#### **FEATURES**

- Available in 25m length
- A voltage rating of 600/1000V
- Single core cable design
- Maximum operating temperature of 70°C

# RS PRO Green/Yellow Single Core x 10.0sqmm (Class 5 PCW), PVC Insulated, 600/1000V, Type BK,25m

RS Stock No.: 516-8000



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



## **Product Description**

From RS PRO, comes a range of high quality and great value Tri-rated cables. Manufactured with a premium annealed copper conductor and insulated with PVC (Polyvinyl Chloride), these Tri-rated cables are a fantastic solution for use in control panels and other types of electrical equipment

## **General Specifications**

Туре	BK
Tri-rated	No
Sheath Colour	Yellow/Green
Fire Behaviour	Flame Retardant
Application	Electrical cabinets, Industrial electrical installations, Small electronic devices, Relay and instrumentation panels, Control metering, Motor starters

#### **Electrical Specifications**

Voltage Rating	600/1000V
Current Rating	68A
Conductor Material	72/0.40mm Plain Annealed Copper (Class 5 to IEC 60228)
Insulation Material	PVC (Type TI1 to BS EN 50363)
Conductor Resistance	1.91 Ω/km @ 20°C (Maximum)

#### **Mechanical Specifications**

Length	25m
Cross Sectional Area	10mm <sup>2</sup>
Outer Diameter	7.2mm
American Wire Gauge	7
Core Strands	80/0.4mm
Size of Strands	0.4mm
Insulation Wall Thickness	1.00mm (Nominal)
Minimum Bend Radius	6 x Overall Diameter
Weight	112.90kg/km
Diameter Over Insulation	Lower Limit: 5.70mm;Upper Limit: 7.20mm



# **Operation Environment Specifications**

Temperature Range	-15 to +70°C
i omporataro rtango	10 10 17 0 0

# **Approvals**

tandards Met	BS 6231:2006
--------------	--------------



