

Datasheet Brass Pneumatic Quick Connect Coupling, G 3/8 Male, Threaded

RS Stock number 667-1819

	021 [Quick	Release Pne	umatic Couplir	ngs]		
	Interchangeab	Options				
	RECTUS 2 RECTUS 90, CAMOZZI		F-Straight Through flow K - Chrome Plated			
	Temperature Range -20 C +100 C (-4 F +212 F)		T - NPTF Thread			
	Working Pressure 0 - 35 bar (0 - 500 PSI)		V - Viton Seal			
	Flow Capacity NW - 5		Material Coupler Body : Brass Nickel Plated Sleeve : Steel Body : Brass Nickel Plated			
	Standard version Balls : Stainless Steel Buna (N)		Valve : Brass Springs : Stainless Steel Locking O-Ring : Stainless Steel Balls : Stainless Steel			
			Seals : Buna Plug : Brass		ted	
Couplers and Plugs	Connection	Order	No	SW	Length	Dia
	g 1/8"	021 EG	10	14	36	16
	G 1/4"	021 EG	13	17	38	16
	G 3/8"	021 EG	17	19	38	16
Male Thread Coupler	M 12X1,5	021 EG	12	17	39	16
	M 14X1,5	021 EG	14	17	39	16
Female Thread Coupler	G 1/8"	021 DG	10	14	36	16
	G 1/4"	021 DG	13	17	38	16
	G 3/8"	021 DG	17	19	38	16
	M 12X1,5	021 DG	12	17	38	16
	M 14X1,5	021 DG	14	17	38	16



ENGLISH

	4mm 1/6"	021 HG 04	14	46	16
	6mm 1/4"	021 HG 06	14	46	16
	8mm 5/16"	021 HG 08	14	46	16
	9mm 5/14"	021 HG 09	14	46	16
	10mm 3/8"	021 HG 10	14	46	16
Standart Hose Barb Coupler	6mm Parker 1/4"	021 HG 06 P	14	46	16
Plastic Hose Coupler	4X6mm- M10X1	021 PG 04	14	41	16
	6X8mm- M10X1	021 PG 06	14	41	16
	4X6mm- M10X1	021 SG 04	14	53	16
Plastic Hose Coupler With Spring	6X8mm- M12X1	021 SG 06	17	53	16
	4mm- M10X1	021 MG 04	14	60	16
Standart Hose Barb Plug	5mm- M12X1	021 MG 05	14	60	16
	6mm- M12X1	021 MG 06	17	60	16
	6mm- M12X1	021 MG 08	17	60	16
Plastic Hose Plug	4X6mm- M10X1	021 YG 04	14	125	16
	6X8mm- M10X1	021 YG 06	14	130	16



ENGLISH

	4mm 1/6"	021 HU 04		32	9	
Male Thread Plug	5mm 1/5"	021 HU 05		32	9	
	6mm 1/4"	021 HU 06		32	9	
	8mm 5/16"	021 HU 08		32	9	
	9mm 5/14	021 HU 09		33	12	
	10mm 3/8"	021 HU 10		33	12	
	6mm Parker	021 HU 06 P		36	16	
Female Thread Plug	4X6 mm- M10X1 6X8 mm- M12X1	021 PU 04 021 PU 06		32 32	10 12	
Male Thread Plug	4X6mm- M10X1 6X8mm-	021 SU 04 021 SU 06	14 17	44 44		
Male Thread Plug	M12X1 4 mm- M10X1 5 mm-	021 MU 04	14	50		
	M10X1 6 mm-	021 MU 05	14	50		
	M12X1 8 mm-	021 MU 06	14	50		
	M12X1	021 MU 08	14	50		
	9 mm- M12X1	021 MU 09	14	50		
	10 mm- M14X1	021 MU 10	17	50		



ENGLISH

	4X6mm-	021 YU 04		115
Male Thread Plug	M10X1 6X8 mm- M10X1	021 YU 06		120
	G1/8"	021 EU 10	14	25
	G1/4"	021 EU 13	17	28
Male Thread Plug	G3/8"	021 EU 17	19	28
	M 10X1	021 EU 10 M	14	26
	M 12X1,5	021 EU 12	17	28
	M 14X1,5	021 EU 14	17	28
	G 1/8"	021 DU 10	14	25
	G 1/4"	021 DU 13	17	26
	G 3/8"	021 DU 17	19	27
	M 10X1	021 DU 10 M	14	27
Male Thread Plug	M 12X1,5	021 DU 12	17	27
	M 14X1,5	021 DU 14	17	27