



**RoHS
Compliant**



Specifications

Current Rating	: 3A AC/DC
Voltage Rating	: 250V AC, DC
Temperature Range	: -25°C to +85°C
Contact Resistance	: 20mΩ Max.
Insulation Resistance	: 1000MΩ Min.
Withstanding Voltage	: 1500V AC/minute
Pin Material	: Brass/Gold-flash
Material	: PBT15%GF, UL94V-0
Colour	: Black

Diagram



Part Number Table

Description	Number of Positions	Dimensions		Part Number
		A (mm)	B (mm)	
Pin Header, Wire-to-Board, 2.54mm, Through Hole Straight	10	10.16	20.32	SPC20505
	14	15.24	25.4	SPC20506
	16	17.78	27.94	SPC20507
	20	22.86	33.02	SPC20508
	26	30.48	40.64	SPC20509
	34	40.64	50.8	SPC20510
	40	48.26	58.42	SPC20511

Dimensions : Millimetres

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
sg.element14.com/b/multicomp-pro