



Main

| | |
|---------------------------|-------------------|
| Range | PowerLogic |
| Product name | PowerLogic PM5000 |
| Device short name | PM5320 |
| Product or component type | Power meter |

Complementary

| | |
|---------------------------------|--|
| Power quality analysis | Up to the 31st harmonic |
| Device application | Multi-tariff Power monitoring |
| Type of measurement | Current Voltage Frequency Power factor Energy Active and reactive power |
| Supply voltage | 90...450 V AC 45...65 Hz 100...300 V DC |
| Network frequency | 50 Hz 60 Hz |
| [In] rated current | 1 A 5 A |
| Type of network | 1P + N 3P + N 3P |
| Maximum power consumption in VA | 11 VA at 415 V |
| Ride-through time | 80 Ms 120 V AC typical 100 Ms 230 V AC typical 100 Ms 415 V AC typical 50 ms 125 V DC typical |
| Display type | Monochrome graphic LCD |
| Display resolution | 128 x 128 pixels |
| Sampling rate | 64 samples/cycle |
| Measurement current | 5...8500 mA |
| Analogue input type | Voltage (impedance 5 MOhm) Current (impedance <= 0.3 mOhm) |
| Measurement voltage | 35...760 V AC 45...65 Hz between phases 20...440 V AC 45...65 Hz between phase and neutral |
| Frequency measurement range | 45...65 Hz |
| Number of inputs | 2 digital |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|-----------------------------|---|
| Measurement accuracy | Active energy +/- 0.5 % Reactive energy +/- 2 % Active power +/- 0.5 % Apparent power +/- 0.5 % Frequency +/- 0.05 % Power factor +/- 0.5 Current +/- 0.5 % Voltage +/- 0.5 % Apparent energy +/- 0.5 % Reactive power +/- 2 % |
| Accuracy class | Class 0.5S active energy conforming to IEC 62053-22 |
| Number of outputs | 2 digital |
| Information displayed | Tariff (4) |
| Communication port protocol | Modbus TCP/IP at 10/100 Mbit/s, insulation 2500 V BACnet IP |
| Communication port support | ETHERNET |
| Data recording | Maintenance logs Alarm logs Min/Max of instantaneous values Event logs Time stamping Data logs |
| Memory capacity | 256 kB |
| Connections - terminals | Voltage circuit: screw terminal block4 Control circuit: screw terminal block2 Current transformer: screw terminal block6 Input/Output circuit: screw terminal block6 Relay output: screw terminal block4 Ethernet network: RJ45 connector |
| Mounting mode | Flush-mounted |
| Mounting support | Framework |
| Standards | IEC 62053-22 EN 50470-1 IEC 60529 IEC 61557-12 UL 61010-1 EN 50470-3 IEC 62053-24 |
| Product certifications | CE conforming to IEC 61010-1 CULus conforming to UL 61010-1 |
| Width | 96 mm |
| Depth | 72 mm |
| Height | 96 mm |
| Net weight | 430 g |

Environment

| | |
|---------------------------------------|---|
| Electromagnetic compatibility | Limitation of voltage changes, voltage fluctuations and flicker in low-voltage class A conforming to IEC 61000-3-3 Electrostatic discharge - test level: 8 kV level 4 conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test level 3 conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test level 4 conforming to IEC 61000-4-4 Surge immunity test level 4 conforming to IEC 61000-4-5 Voltage dips and interruptions immunity test conforming to IEC 61000-4-11 Limits for harmonic current emissions class A conforming to IEC 61000-3-2 Conducted RF disturbances level 3 conforming to IEC 61000-4-6 Magnetic field at power frequency level 4 conforming to IEC 61000-4-8 Conducted and radiated emissions class B conforming to EN 55022 Limitation of voltage changes, voltage fluctuations and flicker in low-voltage conforming to IEC 61000-3-3 Radiated radio-frequency electromagnetic field immunity test conforming to IEC 61000-4-3 |
| IP degree of protection | IP54 display: conforming to IEC 60529 IP30 rear: conforming to IEC 60529 |
| Relative humidity | 5...95 % at 50 °C non-condensing |
| Pollution degree | 2 |
| Ambient air temperature for operation | -25...70 °C meter -20...70 °C display -25...-20 °C (with reduced performance) display |

| | |
|-------------------------------------|---------------------------------|
| Ambient air temperature for storage | -40...85 °C |
| Operating altitude | 2000 m CAT III 3000 m CAT II |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 11.0 cm |
| Package 1 Width | 12.6 cm |
| Package 1 Length | 12.6 cm |
| Package 1 Weight | 550.0 g |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 12 |
| Package 2 Height | 30.0 cm |
| Package 2 Width | 30.0 cm |
| Package 2 Length | 40.0 cm |
| Package 2 Weight | 7.096 kg |
| Unit Type of Package 3 | P12 |
| Number of Units in Package 3 | 288 |
| Package 3 Height | 105.0 cm |
| Package 3 Width | 80.0 cm |
| Package 3 Length | 120.0 cm |
| Package 3 Weight | 206.4 kg |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |