




DIMENSIONS mm (inches)



PCB DRILLING



PART NUMBER	8609	<input type="checkbox"/>	<input type="checkbox"/>	71	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	5	<input type="checkbox"/>
PIN OUT									
rows a-b-c				3				96	
rows a-c				4				64	
NUMBER OF CONTACTS									
TERMINATION									
L = 2.75 ±0.15 (.108)				A = ∅0.6 ⁰ -0.08				B = ∅0.8 ^{+0.3}	13
OPTIONS									
no option									7
with harpoons								for PCB thickness 1.6 mm	H
PERFORMANCE CLASS									
DIN 41612 class 3									4
DIN 41612 class 2									5
DIN 41612 class 1									6
TERMINATION TYPE									
TIN LEAD									-485E1
LEAD FREE									-ATLF

SPECIFICATION 485 or ATLF

specific marking : customer part number + date code

GENERAL CHARACTERISTICS and ROHS INFORMATIONS
SEE DRAWING C-8609-0000A

Copyright FCI.

European Views

rev	ecn no	dr	date
A	-	ROU	2000/11/20
B	LS07-0130	HLE	2007/06/04
C	LS07-0211	HLE	2007/08/09
-	-	-	-
-	-	-	-
-	-	-	-

www.fciconnect.com		surface ISO 1302 <input checked="" type="checkbox"/>	tolerance std ISO 406 ISO 1101	projection 	mm
TOLERANCES UNLESS OTHERWISE SPECIFIED					
Dr	ROUILLARD	2000/11/20	ANGULAR	0.X	±0.1
Eng	ROUILLARD	2000/11/20	LINEAR	0.XX	±0.1
Chr	LEGARE	2000/11/20	0.XX' ±2'	0.XXX	±0.1
Appr	LEGARE	2000/11/20	Product family	DIN	Spec ref -
title RIGHT ANGLE MALE STYLE C SOLDER TO BOARD				dwg no C-8609-0849	Rev. C
catalog no			SEE TABLE	CUSTOMER	sheet 1 of 1

