



# Datasheet

## RS PRO BOXED METRIC NYLON TUBING SERIES

Stock number: See Table

Industrial tubing made from flexible nylon. Ideally suited for pneumatic/hydraulic applications such as air brakes, as well as fuel and lube applications.

Also ideal for low toxic or high temperature environments such as breweries or applications involving food contact.

### Key Features:



- Flexible, lightweight and durable over a wide temperature range.
- Smooth inner for improved flow.
- Manufactured from heat and light stabilised Nylon to precise tolerances.
- Available on dispensing drums.
- Boxed available for minimum order quantities.
- Resistant to a wide range of chemicals.
- High resistance to moisture absorption.
- Manufactured in accordance with BS 5409, DIN 73378, DIN 74324 and ISO 7628.
- Silicone-free.
- Excellent abrasion resistance.
- 4:1 safety factor.
- RoHS 3 compliant.
- REACH compliant.

### Sizes:

Available in 30m coils

### Colours:

Natural, black, blue, red, green and yellow



Product Ref	Colour	Internal Diameter	External Diameter	Maximum Working Pressure	Minimum Burst Pressure	Weight per Metre	Bend Radius	Length
2020948	Natural	2.5mm	4mm	26 Bar	104 Bar	0.008 Kg	25mm	30m
2020950	Black	2.5mm	4mm	26 Bar	104 Bar	0.008 Kg	25mm	30m
2020951	Blue	2.5mm	4mm	26 Bar	104 Bar	0.008 Kg	25mm	30m



1. Impact modified PA12



### Applications:

- Pneumatics
- Air brake, fuel and lube applications
- Production lines (industrial and automotive)

### Packaging:

Supplied boxed for ease of handling.



## Datasheet

# RS PRO BOXED METRIC NYLON TUBING - NMF SERIES

Stock number: See Table

Product Ref	Colour	Internal Diameter	External Diameter	Maximum Working Pressure	Minimum Burst Pressure	Weight per Metre	Bend Radius	Length
2020952	Red	2.5mm	4mm	26 Bar	104 Bar	0.008 Kg	25mm	30m
2020953	Yellow	2.5mm	4mm	26 Bar	104 Bar	0.008 Kg	25mm	30m
2020954	Green	2.5mm	4mm	26 Bar	104 Bar	0.008 Kg	25mm	30m
2020956	Natural	4mm	6mm	24 Bar	96 Bar	0.017 Kg	35mm	30m
2020957	Black	4mm	6mm	24 Bar	96 Bar	0.017 Kg	35mm	30m
2020958	Blue	4mm	6mm	24 Bar	96 Bar	0.017 Kg	35mm	30m
2020959	Red	4mm	6mm	24 Bar	96 Bar	0.017 Kg	35mm	30m
2020960	Yellow	4mm	6mm	24 Bar	96 Bar	0.017 Kg	35mm	30m
2020962	Green	4mm	6mm	24 Bar	96 Bar	0.017 Kg	35mm	30m
2020963	Natural	5.5mm	8mm	22 Bar	88 Bar	0.029 Kg	45mm	30m
2020964	Black	5.5mm	8mm	22 Bar	88 Bar	0.029 Kg	45mm	30m
2020965	Blue	5.5mm	8mm	22 Bar	88 Bar	0.029 Kg	45mm	30m
2020966	Red	5.5mm	8mm	22 Bar	88 Bar	0.029 Kg	45mm	30m
2020967	Yellow	5.5mm	8mm	22 Bar	88 Bar	0.029 Kg	45mm	30m
2020968	Green	5.5mm	8mm	22 Bar	88 Bar	0.029 Kg	45mm	30m
2020969	Natural	7mm	10mm	22 Bar	88 Bar	0.039 Kg	60mm	30m
2020970	Black	7mm	10mm	22 Bar	88 Bar	0.039 Kg	60mm	30m
2020971	Blue	7mm	10mm	22 Bar	88 Bar	0.039 Kg	60mm	30m
2020972	Red	7mm	10mm	22 Bar	88 Bar	0.039 Kg	60mm	30m
2020973	Yellow	7mm	10mm	22 Bar	88 Bar	0.039 Kg	60mm	30m
2020974	Green	7mm	10mm	22 Bar	88 Bar	0.039 Kg	60mm	30m
2020975	Natural	8.5mm	12mm	21 Bar	84 Bar	0.055 Kg	70mm	30m
2020976	Black	8.5mm	12mm	21 Bar	84 Bar	0.055 Kg	70mm	30m
2020978	Blue	8.5mm	12mm	21 Bar	84 Bar	0.055 Kg	70mm	30m
2020979	Red	8.5mm	12mm	21 Bar	84 Bar	0.055 Kg	70mm	30m
2020980	Yellow	8.5mm	12mm	21 Bar	84 Bar	0.055 Kg	70mm	30m
2020981	Green	8.5mm	12mm	21 Bar	84 Bar	0.055 Kg	70mm	30m