

## FEATURES

- Shrink ratio: 2:1
- High temperature resistant polyolefin
- Very flexible, high flame retardant (colors only)
- Resistant to common solvent liquid
- Excellent physical, chemical and electrical performance
- Compliance with RoHS
- Longitudinal change - 10%~10%
- Continuous operating temperature: - 55°C~135°C
- Minimum shrink temperature: 70°C
- Full recovery temperature: Above 110°C

## RS PRO 135°C heat shrinkable polyolefin tubing

RS Stock No.: 2345905



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

**Product Description**

The military grade 135C is an environmental friendly polyolefin material tubing and used in military, industrial and commercial applications. The higher temperature rating provides more reliable protection for the product covered. It can be applied to outer insulation protection of wire splices and electronic components.

**General Specifications**

Part Number	As supplied (mm)	After recovered (mm)		Length / Roll (Meter)
	I.D.(min)	I.D.(max)	W.T.	
2345905	6.4	3.2	0.64±0.08	8

## Additional Information

<b>EAN</b>	
<b>Custom Tariff Number</b>	39173900

## Classification

<b>eCl@ss</b> (Version)	
<b>UNSPSC</b> (Version)	

## Approvals

<b>Declarations</b>	RoHS Reach
<b>Hazardous Area Certification</b>	
<b>Standards Met</b>	