

FEATURES

- Fits standard XLR Ø24mm cutout.
- No soldering or punch termination. Use standard cable for each connector style.
- Front or rear mounted.
- Low rear profile
- 90° or right angle rear cable entry.

RS PRO HDMI Right Angle Feedthrough Connectors

RS Stock No.: 2576704



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

HDMI Right angle feedthrough connector. A feedthrough, data connector for electrical instrumentation. Used for developing custom I/O configurations for wall plates, rack panels, etc.

Common cabling can be used for front and rear connections. No soldering and no punch terminations - just use the standard cable for that particular connector style.

XLR format feedthrough connectors fit within a standard XLR panel cutout and can be mounted from the front or back. A low rear profile accommodates the tightest behind-the-panel spaces.

Please note: Functionality is affected by cable quality, length and cable wiring configuration.

General Specifications

| | |
|--------------------------------------|---|
| Gender | Female |
| Number of Contacts | 19 |
| Size | Ø24mm cutout |
| Contact Material | Brass |
| Contact Plating | Gold plating |
| Body Orientation | Right angle |
| Termination Method | Feed through |
| Housing Material | Insert: ABS UL94-V2 Frame: Polyamide UL94-V2 |
| Colour | Black |
| Maximum Operating Temperature | Max +60°C |
| Minimum Operating Temperature | Min -10°C |

Mechanical Specifications

| | |
|----------------------|------------------|
| Mounting Hole | CSK hole |
| Frame Style | Plastic XLR type |

Approvals

| | |
|----------------------------------|-------------|
| Compliance/Certifications | REACH, RoHS |
|----------------------------------|-------------|

HDMI Feedthrough Connectors

