



ENGLISH

Datasheet

Stock No: 815-672

RS Pro Feed Through Terminal Block, RK Series



Product Details

Standard Feed Through

DIN rail mounted terminals, with universal mounting foot clips to both 'G' profile (asymmetric to BS5825:1990) and 'top hat' profile (symmetric to BS5584:1978) rails, with a range of features to suit all applications. The 2.5 to 10mm² terminals have common end covers and partitions, there are 10 pole Jumper Bars available for cross connection and are easily fitted with markers on either side.

Note

Please see jumper bars for compatibility

Approvals

UL, CSA, NEMKO, GOST

RS DIN Rail Terminals 2

Approvals

UL, CSA



ENGLISH

Compatibility Table			
Stock number	End cover	Pre-assy jumper bar	Markers
815-638	815-650	815-789	460-610
815-644	815-650	815-789	460-610
802-777	815-688	-	460-610
802-783	815-688	-	460-610
815-666	815-688	815-795	460-610
815-672	815-688	815-795	460-610
815-694	815-688	815-802	460-610

Specifications:

Series	RK
Wire Size	22 → 11 AWG
Cable CSA	0.2 → 4mm ²
Colour	Blue
Current Rating	40A
Termination Method	Screw Down
Voltage Rating	800 V
Minimum Operating Temperature	-40°C
Maximum Operating Temperature	+105°C