



Description

The series of medium wall general purpose tubing is specially designed for use in a broad range of low-voltage applications. Tough and flexible, the tubing is particularly suited for the insulation and protection of cable joints as well as for cable repair. Uncoated tubing provides insulation and strain relief. Adhesive lined tubing also provides an environmental seal.

Specifications

Operating temperature : -45°C to +125°C
 Fully shrink temperature : 125°C
 Shrink Ratio : 3:1
 Colour : Black
 Resistant to UV

Technical Data

Property	Test Method	Typical Data
Tensile Strength	ASTM D2671	≥14MPa
Elongation	ASTM D2671	≥400%
Density	ASTM D792	1.2g/cm ³
Longitudinal change	UL 224	≤ ±10%
Elongation after aging	UL224 158°C×168hrs	≥300%
Heat shock	UL224 225°C×4hrs	No cracking
Dielectric strength	IEC 243	≥20kV/mm
Volume resistivity	IEC 93	≥10 ¹⁴ Ω.Cm
Water absorption	ASTM-D570	≤0.15%
Flammability	VW-1	Self-extinguish in 30 seconds

Hot Melting Adhesive Property

Property	Test Method	Typical Data
Water absorption	ASTM D570	≤ 0.2%
Softening point	ASTM E28	95°C
Peel strength(PE)	ASTM D1000	120N/25mm
Peel strength(AL)	ASTM D1000	80N/25mm

Product Dimensions

Part Number	Size	As Supplied	After Recovery			
	mm	Internal Diameter (mm)	Internal Diameter (mm)	Out layer Wall Thickness (mm)	Adhesive Layer Wall Thickness (mm)	Total Wall Thickness (mm)
PP001863	10.2/3	≥10.2	≤3	1.43 ±0.4	0.53 ±0.2	1.96 ±0.5
PP001864	19.1/5.6	≥19.1	≤5.6	1.83 ±0.4	0.63 ±0.2	2.66 ±0.5
PP001865	28/9	≥28	≤9	1.95 ±0.4	0.78 ±0.2	2.73 ±0.5
PP001866	38.1/12	≥38.1	≤12	2.05 ±0.4	0.78 ±0.2	3.13 ±0.5
PP001867	43.2/12.7	≥43.2	≤12.7	2.15 ±0.4	0.78 ±0.2	3.13 ±0.5
PP001868	63/19	≥63	≤19	2.35 ±0.5	0.88 ±0.3	3.53 ±0.6

Part Number Table

Description	Part Number
Tubing, Heat Shrink, Medium Wall, W/Adhesive, 3:1, 9mm, Black, 1.22m	PP001863
Tubing, Heat Shrink, Medium Wall, W/Adhesive, 3:1, 19.1mm, Black, 1.22m	PP001864
Tubing, Heat Shrink, Medium Wall, W/Adhesive, 3:1, 28mm, Black, 1.22m	PP001865
Tubing, Heat Shrink, Medium Wall, W/Adhesive, 3:1, 38.1mm, Black, 1.22m	PP001866
Tubing, Heat Shrink, Medium Wall, W/Adhesive, 3:1, 43.2mm, Black, 1.22m	PP001867
Tubing, Heat Shrink, Medium Wall, W/Adhesive, 3:1, 63mm, Black, 1.22m	PP001868

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.