

# **PRODUCT DATA SHEET**REXCO 70-MULTI PURPOSE DEGREASER



#### PRODUCT DESCRIPTION

**REXCO 70 MULTIPURPOSE DEGREASER** is a degreaser product is a product to remove oil, grease, dirt, & dust as well as shine & protect metal surfaces. So it is ideal for industry, automotive and household.

**REXCO 70 MULTIPURPOSE DEGREASER** An all-purpose degreaser that has a specific mode of action, which is to dissolve and remove dirt that sticks to the surface of hard objects such as metal.

The foam in **REXCO 70 MULTIPURPOSE DEGREASER** adheres to the engine surface to penetrate deeply and quickly remove stubborn oil and dirt on the engine block. Foaming water-based formula aggressive enough to break down and dissolve grease, grime, oil, rubber marks, and other oil-based contaminants

**REXCO 70 MULTIPURPOSE DEGREASER** products have undergone extensive testing by in-house and third-party scientists, vehicle repair shops, and professional mechanics as well as involved industry parties. Applications: marine parts, exteriors, interiors, maintenance equipment, painted surfaces, chrome & Stainless Steel metallic parts and heavy machinery.

## **PRODUCTS**



500 ML

## **PRODUCT APPLICATIONS**

- Engines
- Hand & Power Tools
- Household Appliances
- Industrial Machinery
- Chain Drives
- Kitchen Stoves
- Exhaust Hoods & Hobs

### **ADVANTAGES & FEATURES**

- REXCO 70 MULTIPURPOSE DEGREASER Product does not contain chlorofluorocarbons (CFCs), (HCFCs).
- EXCO 70 MULTIPURPOSE DEGREASER Product does not contain Lead (Pb), Mercury (Hg), Cadmium (Cd), Hexavalent Chromium (Cr6), Polybrominated biphenyls (PBB), or Polybrominated diphenylether complying of the RoHS certificate.
- Quality testing involves a third party that has obtained ISO/IEC 17052 certificate.
- Removes oil, grease, dirt and dust.
- Keeps the metal surfaces of the machine looking like new.
- Fast and easy usage.
- Leaves no residue.
- Clean power faster and more effectively with foam cleaning.
- Can be used at the level of segmentation of use both industrial, household and automotive.
- Special blend of surfactants, detergents, emulsifiers and foaming to lift dirt.
- Non-corrosive, non-staining and non-conductive.
- Acetone free.
- Chlorine free.

#### **DIRECTIONS FOR USE**

- Shake the canister well before use.
- Test compatibility with plastics and rubbers and painted surface prior application.
- Do not spray on hot surfaces (cover all electrical components with plastic sheet). Spray directly onto surface to be cleaned. Allow for several minutes. For thicker dirt and grease, loosen with brush. Then rinse with water.
- Use 360° valve, can be sprayed in any direction.
- · Save to use on fabric, plastic, paint, and other finishes.
- CAUTIONS: Flammable. Pressurized container, protect form direct sun light. Do not expose to temperature exceeding 50°C. Do not pierce or burn, even product runs out. Do not spray on direct flame or any flammable material – Do Not Use While Smoking. Use in well ventilated area only.
- KEEP OUT OF REACH OF CHILDREN. Contains distillates (petroleum), hydro treated light.

| TECHNICAL DATA TEST         |       |                     |                                 |
|-----------------------------|-------|---------------------|---------------------------------|
| PARAMETERS                  | UNITS | TYPICAL DATA        | METHODS                         |
| Appearance                  | -     | Clear & White Foam  | Visual                          |
| Odor                        | -     | Soap & solvent odor | -                               |
| Solubility in Water         | -     | Soluble in Water    | -                               |
| Specific Gravity at 27°C    | -     | 1.0152              | ASTM D4052-11                   |
| Color ASTM                  | -     | L 0.5               | ASTM D1500-12                   |
| Kinematic Viscosity at 27°C | cSt   | 2.766               | ASTM D445-14                    |
| Flash Point COC             | °C    | Below 79            | ASTM D92-12b                    |
| Boiling Point               | °C    | 94.0                | ASTM D1120-94 (Reapproved 2004) |
| PH                          | -     | 11.70               | Potentiometric                  |