



ENGLISH

Datasheet

**RS Pro Fixed Plate Castor Art54A 260mm, 150kg**

RS Stock No: **666-7606**



## Product Details

RS Pro fixed castor wheel Art54A has diameter of 260 mm and load capacity of 150 kg. Soft tread wheels are kinder to floors and quieter in use but are not quite so easy to move from a standing start. For light, medium and heavy duty loads, soft tread wheels offer many benefits. Softer tread tyres are also particularly suitable for power towing applications. For very high load manual handling applications, soft tread wheels should be ruled out as, although they may be capable of carrying a very high load, the force required to move equipment from a standstill would require the efforts of several men.

## Features and Benefits

- Robust castors with roller bearings for smooth running and shock resistance
- Pressed steel centre
- Rubber tyre
- Wide tread makes them suitable for soft surfaces

**Specifications:**

Features	Shock Absorbing, Smooth Running
Fixing Centres (Length)	150 mm
Fixing Centres (Width)	115 mm
Fixing Centres	150 x 115 mm
Fixing Hole Size	26 x 14 mm
Fixing Plate Dimensions	200 x 160 mm
Fixing Plate Length	200 mm
Fixing Plate Width	160 mm
Hub Bearing Type	Roller Bearing
Hub Material	Steel
Includes Brake	No
Load Capacity	150 kg
Number of Fixing Holes	4
Overall Height	302 mm
Rotation	Fixed
Tyre Material	Rubber
Wheel Diameter	260 mm
Wheel Width	85 mm