



Main

Range	ZENcelo
Device application	Power supply
Product or component type	Power socket-outlet
Outlet poles configuration	2P
Load type	Resistive
Colour tint	White

Complementary

Device mounting	Flush Surface
Local signalling	Mechanical indicator (amber)
Clamping connection capacity	2 x 4 mm ² 3 x 2.5 mm ²
Rated current	13 A at 250 V AC 50 Hz
Number of gangs	1 gang
Material	Brass contact Phosphor contact Polycarbonate base Polycarbonate grid plate Polycarbonate surround
Connections - terminals	Folded terminal
Width	87 mm
Height	87 mm
Depth	8 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	UV resistant indoor use
Operating altitude	2000 m
Standards	BS 1363-2 MS 589 SS 145
Standards	BS 1363-2 MS 589 SS 145

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	122.875 g
Package 1 Height	3 cm
Package 1 Width	8.72 cm
Package 1 Length	8.72 cm

Unit Type of Package 2	PAL
Number of Units in Package 2	1600
Package 2 Weight	196600.0 g
Package 2 Height	86 cm
Package 2 Width	80 cm
Package 2 Length	120 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	8
Package 3 Weight	983.0 g
Package 3 Height	15 cm
Package 3 Width	19 cm
Package 3 Length	8 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information