



ENGLISH

## Datasheet

### Stock No.184-5597

# RS PRO Capacitive Sensor



### Specifications:

Mounting: Non flush  
Rated distance Sn: 8mm(adjustable)  
Assured distance Sa: 0...6.4mm  
Shape size: M18\*78mm  
Output way: AC2 wires  
Output status: NO  
Supply voltage: 20...250 VAC  
Standard target: Fe18\*18\*1t  
Switch point offset[%/Sr]:  $\leq \pm 20\%$   
Hysteresis range [%/Sr]: 3...20%  
Repeated error:  $\leq 3\%$   
Load current:  $\leq 300\text{mA}$   
Residual voltage:  $\leq 10\text{V}$   
Current consumption:  $\leq 3\text{mA}$   
Protection circuit: .....  
Output indicator: Yellow LED  
Ambient temperature:  $-25^{\circ}\text{C} \dots 70^{\circ}\text{C}$   
Ambient humidity: 35-95%RH  
Switch frequency: 15 Hz  
High pressure resistance: 1000V/AC 50/60Hz 60s  
Insulation resistance:  $\geq 50\text{M}\Omega(500\text{VDC})$   
Vibration resistance: Complex amplitude 1.5mm 10...50Hz(2H per X,Y,Z direction)  
Protection degree: IP67  
Housing material: Nickel-copper alloy  
Connection: 2m PVC cable

### Features:

- ◆ Be able to detect both metal and nonmetal objects;
- ◆ Be able to detect various media via nonmetallic container;
- ◆ Reliable liquid level detecting;

25/03/2019