

Datasheet
Stock No:1706979
RS Pro N STRAIGHT JACK CLAMP

1.0 ELECTRICAL
 1.1 FREQUENCY RANGE: DC-11 GHz
 1.2 NOMINAL IMPEDANCE: 50 OHMS
 1.3 VOLTAGE RATING: 1000 VOLTS MAX.
 1.4 VSWR: 1.1 MAX. @6 GHz

2.0 MATERIALS
 2.1 BODIES: BRASS PER JIS-C3604
 2.2 CENTER CONTACT: BERYLLIUM COPPER PER ASTM B196 UNS C17300
 2.3 INSULATION: TEFLON PER ASTM D1457 AND ASTM D1710

3.0 FINISHES AND OTHERS
 3.1 SEE BELOW TABLE FOR DETAILS.

4.0 MECHANICAL
 4.1 INTERFACE IN ACCORDANCE WITH: MIL-STD-346A
 4.2 FOR USE WITH LMR400 OR SIMILAR STYLE CABLE
 4.3 CABLE ATTACHMENT: OUTER: CLAMP, INNER: SOLDER

5.0 ENVIRONMENTAL
 5.1 OPERATING TEMPERATURE RANGE: -40° C TO +85° C

NO.	DESCRIPTION	MATERIAL	QTY	FINISH
9	HEAT SHRINK TUBE	PE	1	BLACK (ADHESIVE SHRINK)
8	CENTER CONTACT	BERYLLIUM COPPER	1	GOLD 3μ" MIN.
7	NUT	BRASS	1	WHITE BRONZE 80μ" MIN.
6	WASHER	BRASS	1	WHITE BRONZE 80μ" MIN.
5	GASKET	SILICONE	1	RED
4	BRAID CLAMP	BRASS	1	WHITE BRONZE 80μ" MIN.
3	WASHER	BRASS	1	WHITE BRONZE 80μ" MIN.
2	INSULATION	TEFLON	1	NONE
1	BODY	BRASS	1	WHITE BRONZE 80μ" MIN.

APPROVED by _____ DATE: _____

STRIPPING DIMENSION

DRAWN	TOLERANCE	品名	40610208117001	LMR400	日	DATE	REV.
Jackie	±0.2	TITLE	ROHS COMPLIANT (500)	期	01.04.18	次	A-0
CHECK	XX	UNIT	mm(in)				
APPROVAL	XXX	SCALE					
Jenny	±5°	ANGLE					
		比例					
		3:1					

DESCRIPTION: N STRAIGHT JACK CLAMP
 DWG. NO.: 61-0012-Z