



Main

| | |
|---------------------------|--------------------------|
| Range | Pieno |
| Product or component type | Switch |
| Switch application | Switch |
| Load type | Fluorescent Resistive |
| Cover frame colour tint | Lavender silver |

Complementary

| | |
|------------------------------|---|
| Device mounting | Flush Surface |
| Wiring device mounting | Flush Surface |
| Switch function | 2-way |
| Rated current | 10 AX at 250 V AC 50 Hz |
| Local signalling | Fluorescent (white) |
| Number of gangs | 4 gangs |
| Material | Polycarbonate: surround Polycarbonate: grid plate |
| Connections - terminals | Pillar terminals |
| Clamping connection capacity | 2 x 1.5 mm ² for stranded cable(s) 2 x 2.5 mm ² for solid cable(s) |
| Embedding depth | 23 mm |
| Width | 87 mm |
| Height | 87 mm |
| Depth | 23 mm |

Environment

| | |
|---------------------------------------|------------|
| Ambient air temperature for operation | -5...40 °C |
|---------------------------------------|------------|

| | |
|-------------------|--|
| Relative humidity | 0...95 % |
| Standards | SS 227-1 BS EN 60669-1 GB 16915.1 IEC 60669-1 MS IEC 60669-1 |

Offer Sustainability

| | |
|--------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|